

## IMPACT WRENCH 1" MI-38ELR

This industrial impact wrench by Toku has proven capabilities. The MI-38ELR is developed for tightening and untightening applications. The Twin Hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is especially suitable for use in the tire industry. Characteristics:

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* Power adjustable, 4 positions
- \* Long anvil

## **Related products**



D00100-1-007 Impact Socket Set Long 1" 7-parts



AC40A-F04-D Frl Unit

## **Related accessories**



ATLUB

Air Tool Oil, 1 litre



DOESR-3 Ret Ring

MBC-30S

**Bolt Cleaner Set** 



## **Specifications**

Toku
1"
R+H
36

Impact mechanism Twin-Hammer

RPM 3700
Torque (Nm) 1800
Force adjustment R/L 4 Standen
Airconsumption (I/s) 11,6

Airconsumption (I/s) 11,6

Weight (kg) 7,9

Airconnection PT 1/2"

Airpress max. (MPa) 0,63

mm B 50

Hosediameter (mm) 13

mm A\* 515

Safety standard EN ISO 11148-6 Vibration standard EN ISO 28927-2

Vibration value (m/s²) 12,2

Vibration uncertainty (m/s²) 1,70

Sound standard ISO 15744

Sound pressure (dB(A)) 96

Sound power (dB(A)) 107

Sound uncertainty (dB(A)) 3

EAN 8717981148325

