

# AUTO-SHUT-OFF SCREWDRIVER 6,0~15NM ATEX RRI-SA30315-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIB T135°C.

## Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

## Related products



**TW-3C**

Spring balancer 1,0-3,0 kg



**AC30A-F03E-B**

Modular FRL Unit

## Related accessories



**00-4507**

Torque Adjust Key RRI screwdriver



**ATLUB**

Air Tool Oil, 1 litre



## Specifications

Brand	RedRoosterIndustrial
Bolt capacity (mm)	6
RPM	320
Torque (Nm)	6,0 ~ 15,0
Airconsumption (l/s)	11
Weight (kg)	1,36
Hexagon	1/4"
Sound level (dB(A))	73
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	351
mm B	33
mm C	13
mm D	13,5
mm E	16
Hosediameter (mm)	6,5
Execution	Angle
Vibration level (m/s <sup>2</sup> )	< 2,5
Safety standard	EN ISO 11148-6
EAN	8717981460861

