

# CORDLESS SHUT-OFF ANGLE WRENCH 70 NM RRI-BAW70S3

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

#### Characteristics:






- Brushless motor
- Lithium-Ion battery, choice for 2,5 Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Compact and light weight

Battery and charger to be ordered separately. The reaction bar 31022-WR00 is included in the delivery.

#### Related products

|   |  |
|---|--|
|  | <b>DWL-B</b><br>2.4G/5.8G WLAN receiver        |
|  | <b>BB200D-325</b><br>18V 2.5Ah Battery, Li-ion |
|  | <b>B74SC180B</b><br>Programmer                 |
|  | <b>BB200D-350</b><br>18V 5.0Ah Battery, Li-ion |
|  | <b>B84192B</b><br>18-20V Charger               |

#### Related accessories

|   |   |
|---|---|
|  | <b>33116-B200D-01</b><br>Protection Cover           |
|  | <b>61022-TH005</b><br>Tool Holder                   |
|  | <b>33116-B200D-02</b><br>Protection Cover           |
|   | <b>31022-WR00</b><br>Reaction Bar for RRI-BA70/90   |
|  | <b>00-4507</b><br>Torque Adjust Key RRI screwdriver |
|  | <b>C16WRB70</b><br>Protection Cover RRI-BA70        |



#### Specifications

|  |                      |
|--|----------------------|
| <b>Brand</b>                                   | RedRoosterIndustrial |
| <b>Square Drive</b>                            | 3/8"                 |
| <b>Bolt capacity (mm)</b>                      | 8 - 12               |
| <b>RPM</b>                                     | 160                  |
| <b>Torque (Nm)</b>                             | 30 - 70              |
| <b>Weight w/o battery (kg)</b>                 | 2,5                  |
| <b>mm A</b>                                    | 535                  |
| <b>mm B</b>                                    | 50                   |
| <b>Battery voltage (Volt)</b>                  | 18                   |
| <b>Battery type Li-ion....(Ah)</b>             | 2,5 - 5,0            |
| <b>Safety standard</b>                         | EN ISO 11148-6       |
| <b>Vibration standard</b>                      | EN ISO 28927-2       |
| <b>Vibration value (m/s<sup>2</sup>)</b>       | 18                   |
| <b>Vibration uncertainty (m/s<sup>2</sup>)</b> | 1,5                  |
| <b>Sound standard</b>                          | ISO15744             |
| <b>Sound pressure (dB(A))</b>                  | 69,2                 |
| <b>Sound uncertainty (dB(A))</b>               | 3                    |
| <b>EAN</b>                                     | 8717981452842        |

