

ANGLE GRINDER 125MMX22MM G-50EF

This angled grinder by Yokota is used for grinding and cutting. Very high quality level. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * For cutting and grinding purposes
- * Exhaust silenced
- * Vibrationreduced deadhandle

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



1203-0013-00-11
Dead Handle Vibration Red.

1120-0655-00-01
Outer Wheel Screw

8100-2001-00-00
Forked Wrench G-40/G-50



1117-0653-00-02
Inner Flange 22 Mm



1117-0654-00-01
Outer Flange 16 Mm

8100-1003-00-00
Bar Wrench G-40/G-50



1117-0654-00-02
Outer Flange 22 Mm



1126-0655-00-00
Outer Wheel Screw

1120-0658-00-01
Pad Flange



1117-0653-00-01
Inner Flange 16 Mm

9310-3004-00-00
Rubber pad G-50



ATLUB
Air Tool Oil, 1 litre

9310-3004-00-99
Rubber Pad(125) In Set With Flanges

8100-3001-00-00
L-Wrench G-40/G-50



Specifications

Brand	Yokota
RPM	12000
Airconsumption (l/s)	10,8
Weight (kg)	1,5
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	299
mm B	88
mm C	29
mm D	50
Hosediameter (mm)	10
Spindle	7/16"
Power (kW)	0,60
Wheel size (mm)	125 x (0,8 - 7) x 22,2
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-1
Vibration value (m/s ²)	3,3
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	84
Sound power (dB(A))	95
Sound uncertainty (dB(A))	3
EAN	8717981000081

