

ANGLE GRINDER 180MMX22MM TAG-700QJL

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * For cutting and grinding purposes
- * Exhaust silenced
- * Low vibration level

Related accessories

-  **2400-046-11**
Dead Handle Vibration Red.
-  **2700-041-00**
Set Screw
-  **2700-040-00**
Wheel Ring
-  **9610-1010-00-00**
Hex Wrench H10
-  **ATLUB**
Air Tool Oil, 1 litre
-  **8081-0022-00-00**
Spanner TAG-700QJL / TAG-900QJL



Specifications

| | |
|--|------------------------|
| Brand | Toku |
| RPM | 8500 |
| Airconsumption (l/s) | 16,6 |
| Weight (kg) | 3,1 |
| Airconnection | PT 3/8" |
| Airpress max. (MPa) | 0,63 |
| mm A | 307 |
| mm B | 103 |
| mm C | 36 |
| mm D | 62 |
| Hosediameter (mm) | 13 |
| Spindle | Toku System |
| Power (kW) | 1,10 |
| Wheel size (mm) | 180 x (1,6 - 8) x 22,2 |
| Vibration standard | EN ISO 28927-1 |
| Vibration value (m/s²) | 9,0 |
| Vibration uncertainty (m/s²) | 2,95 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 87 |
| Sound power (dB(A)) | 98 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981000623 |

