

# ANGLE GRINDER 115MMX22MM G-40EF

This angled grinder by Yokota is used for grinding and cutting. Very high quality level. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal.

#### Characteristics:

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* For cutting and grinding purposes
- \* Exhaust silenced
- \* Vibrationreduced deadhandle

#### Related accessories



1203-0013-00-11

Dead Handle Vibration Red.

9310-3003-00-99

Standard Flanges and outer wheel sc

1120-0655-00-01

Outer Wheel Screw

8100-2001-00-00

Forked Wrench G-40/G-50



1117-0654-00-01

Outer Flange 16 Mm

8100-1003-00-00

Bar Wrench G-40/G-50



1117-0654-00-02

Outer Flange 22 Mm



1126-0655-00-00

Outer Wheel Screw

1120-0658-00-01

Pad Flange



1117-0653-00-01

Inner Flange 16 Mm

9310-3003-00-00

Rubber pad G-40



ATLUB

Air Tool Oil, 1 litre

8100-3001-00-00

L-Wrench G-40/G-50



#### Specifications

Brand	Yokota
RPM	13000
Airconsumption (l/s)	10,8
Weight (kg)	1,4
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	299
mm B	88
mm C	29
mm D	50
Hosediameter (mm)	13
Spindle	7/16"
Power (kW)	0,60
Wheel size (mm)	115 x (0,8 - 7) x 22,2
Vibration standard	EN ISO 28927-1
Vibration value (m/s <sup>2</sup> )	3,3
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	84
Sound power (dB(A))	95
Sound uncertainty (dB(A))	3
EAN	8717981000074

