

# AUTO-SHUT-OFF SCREWDRIVER 0,4 ~ 1,8 NM RRI-SP11602

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

#### **Characteristics:**

- \* New body-design (in composite)
- \* Reversible
- \* Revolving rear-exhaust, silenced
- \* Pistol-version with air on top
- \* ergonomic grip
- \* easily adjustable

### **Related products**



AC30A-F03E-B Modular FRL Unit



HTB-0

**Spring Balancer Hosereel** 

# **Related accessories**



61022-TH001 Tool Holder



00-4507

Torque Adjust Key RRI screwdriver



ATLUB

Air Tool Oil, 1 litre



# **Specifications**


Sound standard

Sound pressure (dB(A))

Sound uncertainty (dB(A))

Brand	RedRoosterIndustrial
Bolt capacity (mm)	4
RPM	1600
Torque (Nm)	0,4 - 1,8
Airconsumption (I/s)	8
Weight (kg)	0,77
Hexagon	1/4"
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	198
mm B	16
mm C	157
Hosediameter (mm)	6,5
Execution	Pistol
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	0,4
Vibration uncertainty (m/s²)	0,53

EAN 8717981279173



ISO 15744

69,2

2