

















AIR HAMMER HEXAGON RRH-2000

Features:

- * Designed and developed for renovation work, the RRH-2000 is a new hammer to the RED ROOSTER programme.
- * The hammer has a very high energy blow per minute but has the advantage of very low weight.
- * An ergonomically designed grip enables both right and left handed use without compromising on comfort.
- * Supplied as standard the hammer is delivered with an open retaining spring to enable the use of both pointed and broad blade chisels.

Related products

-  CB51193180
Slotting Tool W.Carbide Tip L=180
-  CB51112180
Flat Chisel
-  CB51103250
Flat Chisel
-  CB51109165
Flat Chisel
-  CB51112250
Flat Chisel
-  CB51116180
Tail Pipe Cutter
-  CB51123180
Claw Ripper/PannelCutter
-  CB51109180
Flat Chisel
-  CB51109250
Flat Chisel
-  CB51102190
Scraper, bent
-  CB51115250
Moil Point
-  CB51109350
Flat Chisel L=350 W=20mm
-  CB51115180
Moil point chisel
-  CB51114180
Double Bladepanelcutter
-  CB51117180
Spotweld Breaker
-  CB51104190
Wide Cuttingchisbent



Specifications

Brand	RedRooster
Airconsumption (l/s)	8,4
Weight (kg)	1,5
Shank size (mm)	H^11,0 x R12,7 x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	165
mm B	120
Stroke (mm)	42
Strokes per minute	5000
Energy (J/Stroke)	4,5
Hosediameter (mm)	10
Piston (mm)	17,4
Vibration standard	EN ISO 28927-9
Vibration value (m/s ²)	13,75
Vibration uncertainty (m/s ²)	4,98
Sound standard	ISO 15744
Sound pressure (dB(A))	88
Sound power (dB(A))	99
Sound uncertainty (dB(A))	3
EAN	8717981173792

