

AIR CHAIN HOIST 500 KG TCR-500C

These RED ROOSTER Air Chain Hoists are especially developed for heavy industrial use.

Robust cast steel body. Valveblock same for all models, less spare parts. Standard with load limiter.

Characteristics:

- * Precise variable speed control (cord - and pendant control)
- * Optimum control of the load, very precise positioning
- * Compact design
- * Endstop system
- * Load limiter built-in without loss of headroom
- * Cord control or pendant control
- * Quiet, low noise level, silenced
- * Air pressure 0,4 - 0,63 MPa (4 - 6,3 Bar)

Related products



AC40-F04DM-8-B

Modular FRL Unit



6,3X19,1RS60

Chain RSA60 DIN 5684-6



6,3X19,1RTS

Chain RTS EN 818-7



Specifications

Brand	RedRooster
Number of chain falls	1
Lowering speed full load (m/min)	17,9
Lowering speed 0-load (m/min)	13
Weight incl. 3m lift (kg)	31,1
Lifting speed full load (m/min)	10,5
Lifting speed 0-load (m/min)	20,5
Chain weight (kg/m)	0,8
Chain (mm)	6,3 x 19,1
Chainbag/Chainbucket	+
Loadlimiter	+
Airconnection	1/2" BSPT
Airpress max. (MPa)	0,63
mm A	460
mm B	212
mm C	115
mm D	51
mm E	156
mm F	186
mm G	29
mm H	40
mm I	29
mm J	25
mm X	100
mm Y	250
Hosediameter (mm)	13
SMC Airtreatment unit	AC40-F04DM-8-B
Capacity (kg)	500
Air consumption lifting (l/s)	25
Air consumption lowering (l/s)	27
EAN	8717981159987

