

AUTO-SHUT-OFF SCREWDRIVER 1,4~6,5NM ATEX RRI-SA21306-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIB T135°C.

Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

Related products



TW-3C

Spring balancer 1,0-3,0 kg



AC30A-F03E-B

Modular FRL Unit

Related accessories



00-4507

Torque Adjust Key RRI screwdriver



ATLUB

Air Tool Oil, 1 litre



Specifications

Brand	RedRoosterIndustrial
Bolt capacity (mm)	4
RPM	1300
Torque (Nm)	1,4 ~ 6,5
Airconsumption (l/s)	11
Weight (kg)	1,2
Hexagon	1/4"
Sound level (dB(A))	73
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	321
mm B	33
mm C	13
mm D	13,5
mm E	16
Hosediameter (mm)	6,5
Execution	Angle
Vibration level (m/s ²)	< 2,5
Safety standard	EN ISO 11148-6
EAN	8717981460793

