

# HIGH TORQUE GEAR WRENCH 250 NM RRI-BEC025

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. This gear wrench has an extremely high speed.

#### Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

#### Related accessories

-  31022-GW016  
Reaction Welding Ring RRI-BEC025
-  SW40-283-0102  
Hanger
-  31084-360F  
36V Charger
-  31022-GW001  
Reaction Bar RRI-BEC025-250
-  31022-GW010  
Reaction Bar RRI-BEC025-250
-  33257-RRI-BEC025  
Standard Reaction Bar RRI-BEC025
-  31022-GW009  
Reaction Bar RRI-BEC025-250
-  BB360D-325  
36V 2.5Ah Battery, Li-ion
-  31022-GW014  
Sliding Reaction Plate RRI-BEC025
-  BW104  
Back Up Wrench 12-Pt AF 30 mm, max 3254 Nm
-  Koffer RRI-BEC025  
Case RRI-BEC025
-  31022-GW011  
Reaction Bar Adapter RRI-BEC025
-  BB360F-350  
36V 5.0Ah Li-ion Battery



#### Specifications

Brand	RedRoosterIndustrial
Square Drive	1/2"
Bolt capacity (mm)	12 ~ 18
RPM	700 / 75
Torque (Nm)	50 ~ 250
Weight w/o battery (kg)	2,9
mm A	90
mm B	55
mm C	291
mm D	228
mm E	258
mm F	Ø 58
mm L	36
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	1
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	82
Sound uncertainty (dB(A))	3
EAN	8717981444052

