

COMPOSITE IMPACT WRENCH 1" ATEX

RRI-3700ML-EX

This impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-3700ML is developed for assembly- and disassembly applications for wheel bolts and nuts. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use. The high RPM air motor builds up the desired torque levels very fast. With its long anvil this tool is especially well suited for the tire service to trucks and busses.

Breakloose torque: 3.390 Nm.

ATEX classification Ex II 3G IIB T4 – Ex II 3D IIIB 135°C

Characteristics:

- Ergonomic design, well balanced
- Compact design
- Mechoneer Impact mechanism
- Power adjustable, 3 positions, integrated in Forward/Reverse button
- Dead handle 360 degrees adjustable

Related products

- DO4010-0-070-EX
Socket 1" x 70 ATEX
- DO4010-0-055-EX
Socket 1" x 55 ATEX
- DO4010-0-024-EX
Socket 1" x 24 ATEX

Related accessories

- ATLUB
Air Tool Oil, 1 litre
- DOESR-3
Ret Ring



Specifications

Brand	RedRoosterIndustrial
Square Drive	1"
Version	R+H
Bolt capacity (mm)	36
Impact mechanism	Mechoneer
RPM	6000
Torque (Nm)	2700
Force adjustment	R/L 3 Pos
Airconsumption (l/s)	20
Weight (kg)	9,2
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm B	62
Hosediameter (mm)	13
mm A*	500
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	3390
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	12,7
Vibration uncertainty (m/s ²)	1,75
Sound standard	ISO 15744
Sound pressure (dB(A))	108
Sound power (dB(A))	119
Sound uncertainty (dB(A))	3
EAN	8717981459810

