

POKA YOKE IMPULSE WRENCH 3/8 YLA60E-JQ

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air. Exclusively for use with YTC-3 Poka Yoke controller.

Related products



YTC-3*
Poka Yoke+ Controller

Related accessories

0189-0029-00-00


Rubber protection cover YLA60 /70



61022-TH002
Tool Holder, diameter 47mm



ATLUB
Air Tool Oil, 1 litre



Specifications

| | |
|---|----------------|
| Brand | Yokota |
| Bolt capacity (mm) | 6 |
| RPM | 4000 |
| Torque (Nm) | 13 - 22 |
| Airconsumption (l/s) | 5,0 |
| Weight (kg) | 0,78 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 130 |
| mm B | 22 |
| Hosediameter (mm) | 6,5 |
| Square Drive / Hexagon | 3/8" |
| Air consumption no load (l/s) | 5,5 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | < 2,5 |
| Vibration uncertainty (m/s ²) | 1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 71 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981265176 |

