

# AUTO-SHUT-OFF SCREWDRIVER 1,2~3,0NM

## RRI-SA22203

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

### Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

### Related products



**TW-3C**

Spring balancer 1,0-3,0 kg

### Related accessories



**00-4507**

Torque Adjust Key RRI screwdriver



**ATLUB**

Air Tool Oil, 1 litre



### Specifications

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>Bolt capacity (mm)</b>	<b>4</b>
<b>RPM</b>	<b>2200</b>
<b>Torque (Nm)</b>	<b>1,2 - 3,0</b>
<b>Airconsumption (l/s)</b>	<b>11</b>
<b>Weight (kg)</b>	<b>1,2</b>
<b>Hexagon</b>	<b>1/4"</b>
<b>Sound level (dB(A))</b>	<b>73</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>321</b>
<b>mm B</b>	<b>33</b>
<b>mm C</b>	<b>13</b>
<b>mm D</b>	<b>13,5</b>
<b>mm E</b>	<b>16</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Execution</b>	<b>Angle</b>
<b>Vibration level (m/s<sup>2</sup>)</b>	<b>&lt; 2,5</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>EAN</b>	<b>8717981414765</b>

