YOKOTA
CONTROLLED PRECISION IN TIGHTENING

SYSTEM WRENCH 3/4"
YED-200

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Product liability is essential to carmakers. All tightened
joints have to be correct. For this reason all bolted joints must be counted, documented and, of course, tightened with the right clamping force. In order to do this, you need an impulse wrench (with a built-in transducer) connected to a controller. If the controller establishes that the tightened joints do not meet the specifications, it can give a line-stop signal and the
joints have to be checked manually.
Characteristics:
* Very low weight / torque ratio
* High speed fastening
* No Kickback
* Acoustic status-signals on back-cover



Related products



YETC-700A
Controller for TKa transducerized tool



TW-9C
Spring balancer 4,5-9,0kg

Related accessories

0409-0029-00-00
Rubber protection cover YED-200

Specifications

Brand	Yokota
Bolt capacity (mm)	20
RPM	2300
Torque (Nm)	155 - 360
Airconsumption (l/s)	18,3
Weight (kg)	6,8
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	309
mm B	40
Hosediameter (mm)	13
Square Drive / Hexagon	3/4"
Air consumption no load (l/s)	32,2
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	6,6
Vibration uncertainty (m/s²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	86
Sound power (dB(A))	97
Sound uncertainty (dB(A))	3
EAN	8717981179664

