

IMPACT WRENCH 1"

MI-4500ESR

This industrial impact wrench by Toku has proven capabilities. The MI-4500ESR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for the heaviest use in the industry.

Characteristics:

- * Ergonomic design, well balanced
- * Compact
- * Power adjustable, 4 positions

Related products



DO0100-1-007

Impact Socket Set Long 1" 7-parts



AC40A-F04-D

Modular FRL unit

Related accessories



ATLUB

Air Tool Oil, 1 litre



DOESR-3

Ret Ring



Specifications

| | |
|---|----------------|
| Brand | Toku |
| Square Drive | 1" |
| Version | R+H |
| Bolt capacity (mm) | 45 |
| Impact mechanism | Gesloten Hamer |
| RPM | 3700 |
| Torque (Nm) | 2900 |
| Force adjustment | R/L 4 Standen |
| Airconsumption (l/s) | 23 |
| Weight (kg) | 13,4 |
| Airconnection | PT 1/2" |
| Airpress max. (MPa) | 0,63 |
| mm A | 460 |
| mm B | 60 |
| Hosediameter (mm) | 13 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | 11,3 |
| Vibration uncertainty (m/s ²) | 1,62 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 95 |
| Sound power (dB(A)) | 106 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981106509 |

