

# IMPACT WRENCH 1/2

## MI-17MG

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-17MG is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

### Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

### Related products

	<b>D0605201003</b>
	<b>Impact Socket Set 1/2" 10-parts</b>
	<b>D0605222601</b>
	<b>Impact Socket Set 1/2"deep 26-parts</b>
	<b>D0691121301</b>
	<b>Impact Socket Set 1/2" &amp; bits 13-parts</b>
	<b>D069523108</b>
	<b>Impact Socket Set 1/2" deep 10-parts</b>
	<b>D0605202602</b>
	<b>Impact Socket Set 1/2" 26-parts</b>
	<b>D0652260701</b>
	<b>Impact Socket Set 1/2" triple square</b>
	<b>AC30A-F03E-D</b>
	<b>Frl Unit</b>

### Related accessories

	<b>ATLUB</b>
	<b>Air Tool Oil, 1 litre</b>



### Specifications

<b>Brand</b>	<b>Toku</b>
<b>Square Drive</b>	<b>1/2"</b>
<b>Version</b>	<b>R</b>
<b>Bolt capacity (mm)</b>	<b>16</b>
<b>Impact mechanism</b>	<b>Twin-Hammer</b>
<b>RPM</b>	<b>5500</b>
<b>Torque (Nm)</b>	<b>650</b>
<b>Force adjustment</b>	<b>R/L 4 standen</b>
<b>Airconsumption (l/s)</b>	<b>8,8</b>
<b>Weight (kg)</b>	<b>2,5</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>178</b>
<b>mm B</b>	<b>31</b>
<b>Hosediameter (mm)</b>	<b>10</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Max. breakaway torque (Nm)</b>	<b>1450</b>
<b>Vibration standard</b>	<b>EN ISO 28927-2</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>11,2</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>1,60</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>91</b>
<b>Sound power (dB(A))</b>	<b>102</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981357628</b>

