

IMPACT WRENCH 1/2 MI-17MG

This TOKU Impact Wrench has an excellent weigth/power ratio. The MI-17MG is developed for assembly- and disassembly purposes. The Twin Hammer impactmechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- · Exhaust through rubber sealed grip, with silencer

Related products



D0605201003

Impact Socket Set 1/2" 10-parts




D0605222601

Impact Socket Set 1/2"deep 26-parts



D0691121301





AC30A-F03E-B

Modular FRL Unit



D069523108





Impact Socket Set 1/2" deep 10-parts



D0605202602

Impact Socket Set 1/2" 26-parts



D0652260701

Impact Socket Set 1/2" triple square

Related accessories



ATLUB

Air Tool Oil, 1 litre



Specifications

Brand	Toku
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16

Impact mechanism Twin-Hammer

5500 RPM Torque (Nm) 650

Force adjustment R/L 4 standen

Airconsumption (I/s) 22 Weight (kg) 2,5 PT 1/4" Airconnection Airpress max. (MPa) 0.63 178 mm A mm B 31 Hosediameter (mm)

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 1450

EN ISO 28927-2 **Vibration standard**

Vibration value (m/s²) 11,2 Vibration uncertainty (m/s²) 1,60 Sound standard ISO 15744 Sound pressure (dB(A)) 91 102 Sound power (dB(A))

Sound uncertainty (dB(A))

8717981357628 **EAN**

