

# IMPACT WRENCH 1/2 MI-17MG

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-17MG is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

**Characteristics:**

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

**Related products**

-  **D0605201003**  
Impact Socket Set 1/2" 10-parts
-  **D0605222601**  
Impact Socket Set 1/2" deep 26-parts
-  **D0691121301**  
Impact Socket Set 1/2" & bits 13-parts
-  **D069523108**  
Impact Socket Set 1/2" deep 10-parts
-  **D0605202602**  
Impact Socket Set 1/2" 26-parts
-  **D0652260701**  
Impact Socket Set 1/2" triple square
-  **AC30A-F03E-D**  
Frl Unit

**Related accessories**

-  **ATLUB**  
Air Tool Oil, 1 litre



**Specifications**

Brand	Toku
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	5500
Torque (Nm)	650
Force adjustment	R/L 4 standen
Airconsumption (l/s)	8,8
Weight (kg)	2,5
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	178
mm B	31
Hosediameter (mm)	10
Max. breakaway torque (Nm)	1450
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	11,2
Vibration uncertainty (m/s <sup>2</sup> )	1,60
Sound standard	ISO 15744
Sound pressure (dB(A))	91
Sound power (dB(A))	102
Sound uncertainty (dB(A))	3
EAN	8717981357628

