

IMPACT WRENCH 1/2 MI-17MG

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-17MG is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

Related products



D0605201003

Socketset 1/2" 10-Parts



D0605222601

Impact Socket Set 1/2" deep 26 parts



D0691121301

Impact Socket Set 1/2" & bits



AC30A-F03E-B

Modular FRL Unit



D069523108

Socketset 1/2" deep 10-Parts



D0605202602

Impact Socket Set 1/2" - 26 parts



D0652260701

Impact Socket Set 1/2" triple square

Related accessories



ATLUB

Air Tool Oil, 1 litre



Specifications

Brand	Toku
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	5500
Torque (Nm)	650
Force adjustment	R/L 4 standen
Airconsumption (l/s)	8,8
Weight (kg)	2,5
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	178
mm B	31
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	1450
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	11,2
Vibration uncertainty (m/s ²)	1,60
Sound standard	ISO 15744
Sound pressure (dB(A))	91
Sound power (dB(A))	102
Sound uncertainty (dB(A))	3
EAN	8717981357628

