









PAVEMENT BREAKER (25X108MM) RRI-4720K VL

This RED ROOSTER INDUSTRIAL pavement breaker has a chisel retainer with latch. Suitable for endured usage. High energy level each blow. For applications in construction and renovations.

Characteristics:

- Ergonomic design, well balanced
- Compact quality tool
- Integrated noise muffler
- Vibration reduced handle bars

Related products

-  **NC3**
Flat Chisel TL=490 W=25
-  **MP3**
Moil Point TL=500
-  **AC3**
Asphalt Cutter TL=400 W=125
-  **MP3-450**
Moil Point TL= 600
-  **NC3-450**
Flat Chisel TL=600 W=25
-  **NC3-1500**
Flat Chisel TL=1600 W=25
-  **DC3**
Digger steel TL=500 W=75
-  **CB3**
Wide Chisel TL=465 W=75



Specifications

Brand	RedRoosterIndustrial
Airconsumption (l/s)	23
Weight (kg)	22
Shank size (mm)	H [^] 25 x 108
Airconnection	PT 3/4"
Airpress max. (MPa)	0,63
mm A	660
mm B	441
Stroke (mm)	136
Strokes per minute	1200
Energy (J/Stroke)	60
Hosediameter (mm)	19
Piston (mm)	40
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-10
Vibration value (m/s²)	3,4
Vibration uncertainty (m/s²)	1,9
Sound standard	2000/14/EC
Sound pressure (dB(A))	87
Sound power (dB(A))	102
Sound uncertainty (dB(A))	1,9
EAN	8717981427697

