

DIE GRINDER ANGLE 20000 RPM MG-7236B

This angled die-grinder by Toku is used with grinding wheels and burrs with 6mm collet chuck. Application area: Light dressing and fettling on fabrications and die setting sets.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * low vibration level

Related products



AC30A-F03E-B
 Modular FRL Unit

Related accessories



1001-0659-00-01
 Adaptor 3mm for 6mm Chuck



ATLUB
 Air Tool Oil, 1 litre



Specifications

Brand	Toku
RPM	20000
Airconsumption (l/s)	5,0
Weight (kg)	0,45
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	125
mm B	35
mm C	17
mm D	75
Hosediameter (mm)	6,5
Collet chuck (mm)	6
Power (kW)	0,20
Wheel size (mm)	40
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-12
Vibration value (m/s²)	2,3
Vibration uncertainty (m/s²)	0,41
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981012442

