

AIR CHAIN HOIST 12000 KG

TMH-12000C4

The NEW RED ROOSTER TMH series air chain hoists has the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely durable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a full load supporting eye for installation and securing the hoist (during lifting operation) for extra safety.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (80 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

Related products



AC60-F10DM-8-B
Frl Unit



Specifications

| | |
|---|----------------------|
| Brand | RedRooster |
| Airconsumption (l/s) | 58,3 |
| Number of chain falls | 4 |
| Capacity 1st layer (kg) | 12000 |
| Lowering speed full load (m/min) | 2,5 |
| Weight incl. 3m lift (kg) | 190 |
| Lifting speed full load (m/min) | 1,35 |
| Lifting speed 0-load (m/min) | 2,7 |
| Airconnection | 1" PT |
| Airpress max. (MPa) | 0,63 |
| mm A | 856 |
| mm B | 398,5 |
| mm C | 149,5 |
| mm D | 249 |
| mm E | 52 |
| mm F | 309 |
| mm G | 266 |
| mm H | 67 |
| mm I | 75 |
| mm J | 58 |
| mm K | 84 |
| Hosediameter (mm) | 19 |
| Airconnection exhaust | 1" |
| EAN | 8717981340545 |

