

# SCREWDRIVER DIRECT DRIVE RR-1800DD

This RED ROOSTER screwdriver is a direct drive. Intended for light duty use. The direct drive offers proper working conditions for selfdrilling and selftapping screws, as well as work in wood and plastics. Composite body in ergonomic shape to support the operator.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* Exhaust through grip, with silencer
- \* For a long tool-life, the design incorporates needle-bearings

**Related products**



AC30A-F03E-B  
Modular FRL Unit

**Related accessories**

EH-701SUB  
Hose set noise suppressor



ATLUB  
Air Tool Oil, 1 litre



**Specifications**

Brand	RedRooster
Bolt capacity (mm)	6
RPM	1800
Torque (Nm)	7,5
Airconsumption (l/s)	9,8
Weight (kg)	1,0
Hexagon	1/4"
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	175
mm C	165
Hosediameter (mm)	10
Execution	Pistol
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	1,45
Vibration uncertainty (m/s <sup>2</sup> )	0,64
Sound standard	ISO 15744
Sound pressure (dB(A))	83
Sound power (dB(A))	94
Sound uncertainty (dB(A))	3
EAN	8717981196715

