

COMPOSITE IMPACT WRENCH 3/4 RR-24N

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-24N is developed for assembly- and disassembly applications. The Twin Hammer impact mechanism gives high energy levels per impact en thus suitable for heavy duty applications. The energy is directly transmmitted to the anvil for maximum power and low maintenance. The tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Power adjustable, 3 positions
- Exhaust silenced, through grip

Related products



D0605421001

Impact Socket Set 3/4" deep 10-parts



AC40A-F04-D Frl Unit



D0605401001

Impact Socket Set 3/4" 10-parts

Related accessories



DOESR-2 **Ret Ring**



ATLUB



Air Tool Oil, 1 litre



DOESR-1 **Ret Ring**



Specifications

RPM

Brand RedRooster 3/4" **Square Drive** Version R+H 24 **Bolt capacity (mm)**

Impact mechanism Twin-Hammer

5500

10

Torque (Nm) 1625 Force adjustment R 3 Standen 16 Airconsumption (I/s) Weight (kg) 3,7 PT 3/8" Airconnection Airpress max. (MPa) 0.63 210 mm A mm B 50

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 2400

Hosediameter (mm)

EN ISO 28927-2 **Vibration standard**

Vibration value (m/s²) 10,2 Vibration uncertainty (m/s²) 4.08 Sound standard ISO 15744 Sound pressure (dB(A)) 99,78 110.78 Sound power (dB(A))

Sound uncertainty (dB(A))

8717981332519 **EAN**

