




COMPOSITE IMPACT WRENCH 3/4 RR-24N

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RR-24N is developed for assembly- and disassembly applications. The Twin Hammer impact mechanism gives high energy levels per impact and thus suitable for heavy duty applications. The energy is directly transmitted to the anvil for maximum power and low maintenance. The tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Impact mechanism Twin Hammer
- Power adjustable, 3 positions
- Exhaust silenced, through grip

Related products

-  DO605421001
Impact Socket Set 3/4" deep 10p
-  AC40A-F04-D
Modular FRL unit
-  DO605401001
Socketset 3/4" 10-Parts

Related accessories

-  DOESR-2
Ret Ring
-  ATLUB
Air Tool Oil, 1 litre
-  DOESR-1
Ret Ring



Specifications

Brand	RedRooster
Square Drive	3/4"
Version	R+H
Bolt capacity (mm)	24
Impact mechanism	Twin-Hammer
RPM	5500
Torque (Nm)	1625
Force adjustment	R 3 Standen
Airconsumption (l/s)	16
Weight (kg)	3,7
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	210
mm B	50
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	2400
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	10,2
Vibration uncertainty (m/s ²)	4,08
Sound standard	ISO 15744
Sound pressure (dB(A))	99,78
Sound power (dB(A))	110,78
Sound uncertainty (dB(A))	3
EAN	8717981332519

