TOKU

MAKING THE RIGHT IMPACT

IMPACT WRENCH 1"
MI-42ELR

This industrial impact wrench by Toku has proven capabilities. The MI-42ELR is developed for tightening and untightening apllications. The Twin Hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is especially suitable for use in heavy jobs in the tire industry.
Characteristics:
* Ergonomic design, well balanced
* Compact and lightweight
* Power adjustable, 4 positions
* Long anvil



Related products



DO0100-1-007

Impact Socket Set Long 1" 7-parts

Related accessories



ATLUB

Air Tool Oil, 1 litre



DOESR-3

Ret Ring 1"

Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	42
Impact mechanism	Twin-Hammer
RPM	3900
Torque (Nm)	2800
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	23
Weight (kg)	10,6
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm B	60
Hosediameter (mm)	13
mm A*	517
Max. breakaway torque (Nm)	3400
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	15,2
Vibration uncertainty (m/s²)	2,00
Sound standard	ISO 15744
Sound pressure (dB(A))	101
Sound power (dB(A))	112
Sound uncertainty (dB(A))	3
EAN	8717981106493

