

# SYSTEM WRENCH 3/8 TKA700A

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Product liability is essential to carmakers. All tightened joints have to be correct. For this reason all bolted joints must be counted, documented and, of course, tightened with the right clamping force. In order to do this, you need an impulse wrench (with a built-in transducer and angle-encoder on the main shaft) connected to a controller. If the controller establishes that the tightened joints do not meet the specifications, it can give a line-stop signal and the

joints have to be checked manually.

Characteristics:

- \* Very low weight / torque ratio
- \* High speed fastening
- \* No-lube airmotor
- \* No Kickback
- \* Acoustic signals on back-cover

## Related products



**YETC-700A**

Controller for TKa transducerized tool



**SKK**

Tool Holder

## Related accessories



**0341-0018-00-00**

Hanger Ring Heavy Duty



**SO-ITV3050-404BS3-CPL**

Electronic valve for 2-step tightening



**61022-TH003**

Tool Holder, diameter 58mm

**0358-0029-00-00**

Rubber protection cover TKa600/700



**YETC-2 SVD 3/8**

Solenoid valve set



**ATLUB**

Air Tool Oil, 1 litre



## Specifications

Brand	Yokota
Bolt capacity (mm)	6 - 8
RPM	7000
Torque (Nm)	24 - 33
Airconsumption (l/s)	5,3
Weight (kg)	1,34
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	189
mm B	21
Hosediameter (mm)	6,5
Square Drive / Hexagon	1/4" Hex
Air consumption no load (l/s)	6,9
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	< 2,5
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	75
Sound uncertainty (dB(A))	3
EAN	8717981275823

