

# AUTO-SHUT-OFF SCREWDRIVER RRI-SP21104

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

#### Characteristics:

- \* New body-design (in composite)
- \* Reversible
- \* Revolving rear-exhaust, silenced
- \* Pistol-version with air on top
- \* ergonomic grip
- \* easily adjustable

#### Related products



**AC30A-F03E-B**  
Modular FRL Unit

**HTB-0**  
Spring Balancer Hosereel

#### Related accessories



**61022-TH001**  
Tool Holder, diameter 42mm



**00-4507**  
Torque Adjust Key RRI screwdriver



**ATLUB**  
Air Tool Oil, 1 litre



#### Specifications

|   |                      |
|---|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Bolt capacity (mm)                        | 4                    |
| RPM                                       | 1100                 |
| Torque (Nm)                               | 1,5 - 4,0            |
| Airconsumption (l/s)                      | 10                   |
| Weight (kg)                               | 0,98                 |
| Hexagon                                   | 1/4"                 |
| Airconnection                             | PT 1/4"              |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 209                  |
| mm B                                      | 18                   |
| mm C                                      | 157                  |
| Hosediameter (mm)                         | 6,5                  |
| Execution                                 | Pistol               |
| Safety standard                           | EN ISO 11148-6       |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | 0,2                  |
| Vibration uncertainty (m/s <sup>2</sup> ) | 0,51                 |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 69,1                 |
| Sound uncertainty (dB(A))                 | 2                    |
| EAN                                       | 8717981279203        |

