










ROCK DRILL 22X108 TJ-15SV LBS

This vibrationreduced rockdrill of Toku has a latch as retainer. Applicable for time-consuming jobs. High blow-energy. To be used in construction sites and renovations.

Characteristics:

- * Ergonomic design, well balanced
- * Compact quality tool
- * Equipped with exhaust muffler

Related products

-  **CB2261510500**
Drill bars, TL= 500 NL=385
-  **CB2260022**
Monobloc-Drills, Ø22mm L=600mm
-  **CB2261510800**
Drill bars, UL=800
-  **CB6126300032**
Drill bit crosshead, Konus II , Dia
-  **CB6126300030**
Drill bit crosshead, Konus II , Dia
-  **CB6126300034**
Drill bit crosshead, Konus II , Dia
-  **CB6126300050**
Drill bit crosshead, Konus II , Dia
-  **CB2261512000**
Drill bars, NL=2000
-  **CB6126300040**
Drill bit crosshead, Konus II , Dia



Specifications

Brand	Toku
RPM	250
Airconsumption (l/s)	26
Weight (kg)	17,7
Shank size (mm)	H^22 x 108
Airconnection	PT 3/4"
Airpress max. (MPa)	0,63
mm A	468
mm B	340
Stroke (mm)	45
Strokes per minute	2450
Energy (J/Stroke)	44,7
Hosediameter (mm)	19
Piston (mm)	54
Vibration standard	EN ISO 28927-10
Vibration value (m/s²)	10,2
Vibration uncertainty (m/s²)	1,51
Sound standard	ISO 15744
Sound pressure (dB(A))	111
Sound power (dB(A))	122
Sound uncertainty (dB(A))	3
EAN	8717981160051

