

TORQUE WRENCH PRESET 50~300NM WPEMH14300

FEATURES

- Accuracy: Torque: CW \pm 4% from 20% to 100% of capacity;
Angle: (\pm 1% of reading) + (\pm 1° @ angular speed of 10°/s~180°/s) + (\pm 1° of test fixture)
- LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.
- Maintaining the Click audible alarm feature of the mechanical wrench.
- 4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm
- First peak value mode
- Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.
- Peak value and judgment light status remain displayed after unloading.
- WiFi Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.

Related accessories



OH1411

End fitting 14x18, Open End 11 mm

QOH1424

14x18, Open Ring End 24mm



QH1417

End fitting 14x18, Ring End 17 mm



Specifications

Brand	NovaTork
Torque (Nm)	50 ~ 300
Weight (kg)	1,28
insert tool (mm)	14x18
mm D	32
L mm	580
EAN	8717981443826