NovaTork®

TORQUE WRENCH PRESET 50~300NM WPEMH14300

FEATURES

- **Accuracy: Torque: CW±4% from 20% to 100% of capacity; Angle: (±1% of reading) + (±1° @ angular speed of 10°/s~180°/s) +(±1° of test fixture)**
- **LCD screen display, convenient for real-time viewing. The wrench can be adjusted against the displayed torque value.**
- **Maintaining the Click audible alarm feature of the mechanical wrench.**
- **4 Torque units are available: N.m, Ft.lb, In.lb, Kg.cm**
- **First peak value mode**
- **Adjustable mechanism to set the torque value setting, and minimum angle value can be set in the system to prevent the operator from operating the same screw repeatedly.**
- **Peak value and judgment light status remain displayed after unloading.**
- **WLAN Server software can receive instant data from 24 wrenches working at the same time and record the information. Each screen can observe 12 wrenches.**



Related accessories



OH1411

End fitting 14x18, Open End 11 mm



QOH1424

14x18, Open Ring End 24mm



QH1417

End fitting 14x18, Ring End A/F 17mm



DCQ6231

Setting tool PCH models

Specifications

Brand	**NovaTork**
Torque (Nm)	**50 ~ 300**
Weight (kg)	**1,28**
insert tool (mm)	**14x18**
mm D	**32**
L mm	**580**
EAN	**8717981443826**