

COMPOSITE IMPACT WRENCH PISTOL RRI-3700M

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-3700M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use. Breakloose torque: 3.120 Nm.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- · Power adjustable, 3 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown
- dead handle 360 degrees adjustable

Related products



D00100-1-007

Impact Socket Set Long 1" 7-parts



AC40A-F04-D Frl Unit

Related accessories



ATLUB

Air Tool Oil, 1 litre



DOESR-3 Ret Ring



Specifications

Brand RedRoosterIndustrial

 Square Drive
 1"

 Version
 R+H

 Bolt capacity (mm)
 36

Impact mechanism Mechoneer RPM 4300 Torque (Nm) 2300 Force adjustment R/L 3 Pos Airconsumption (I/s) 20 Weight (kg) 6,8 PT 1/2" Airconnection Airpress max. (MPa) 0.63 250 mm A 55 mm B

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 3120

Hosediameter (mm)

Vibration standard EN ISO 28927-2

 Vibration value (m/s²)
 7,2

 Vibration uncertainty (m/s²)
 1,22

 Sound standard
 ISO 15744

 Sound pressure (dB(A))
 103

 Sound power (dB(A))
 114

 Sound uncertainty (dB(A))
 3

EAN 8717981414987

