RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

# DC ELECTRIC SCREWDRIVER 0,05~0,34NM
# RRI-ESL10303

**The RED ROOSTER electrical brushless screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design including ESD safe body material. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This corded tool is designed for the assembly industry, where threaded fasteners are used.**
**Delivery includes: Standard power controller, AC cord and DC cord, clutch cover.**
**Characteristics:**
- **Dual Speed**
- **Reversible**
- **soft ergonomic grip, lever start**
- **starting lever is contactless which allows for high durability**
- **stepless adjustable torque level**
- **the optional clutch cover can prevent unauthorized torque adjustment**



## Related accessories


**TW-06R**
**Spring balancer 0,2-0,6kg**


**DE1L-0012**
**Torque Adjustment Tool**


**DE1L-1078**
**Grip (For lever start)**


**DE1L-0003H**
**Precision Bit 4mm □ 2**


**DE1L-0024**
**Tool Holder**


**DE1L-0003B**
**Precision Bit 4mm □ 00**


**DE1L-2026**
**Clutch Housing Cover**


**DE1L-0003C**
**Precision Bit 4mm □ 0**


**RRI-DE1L-8301**
**Power controller**


**DE1L-0003G**
**Precision Bit 4mm □ 1**

## Specifications

| | |
|---|---|
| **Brand** | **RedRoosterIndustrial** |
| **Bolt capacity (mm)** | **2,0** |
| **RPM** | **270 / 200** |
| **Torque (Nm)** | **0,05 ~ 0,34** |
| **Weight (kg)** | **0,32** |
| **Bitchuck** | **4mm wing** |
| **L mm** | **222,9** |
| **ESD compliance** | **EN IEC 61000-4-2** |
| **Vibration standard** | **EN ISO 28927-2** |
| **Vibration value (m/s²)** | **0,1** |
| **Vibration uncertainty (m/s²)** | **0,0** |
| **Sound standard** | **ISO 15744** |
| **Sound pressure (dB(A))** | **50** |
| **Sound uncertainty (dB(A))** | **3** |
| **EAN** | **8717981470365** |

