RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

18V-3/8" SQ, TRANSDUCER NUTRUNNER RRI-BCA30S3

RED ROOSTER Cordless transducerized angle wrench. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.
Characteristics:
- **Brushless motor**
- **18 Volt Lithium-Ion battery**
- **LED status indicates OK - NOK - REVERSE - BATTERY LOW**
- **Tightening mode setting – Torque or Angle**
- **Programmable torque**
- **Programmable angle limits**
- **Programmable speed**
- **Group check / counting**
- **8 programs including sequence**
- **Compact and light weight**
- **The flat battery pack offers stability**
- **Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately**

Related products



BB200D-325
18V 2.5Ah Battery, Li-ion



BB200D-350
18V 5.0Ah Battery, Li-ion



B84192B
18-20V Charger

Related accessories



33116-B200D-01
Protection Cover



61022-TH005
Tool Holder



32088-NPA-01
Cable



33116-B200D-02
Protection Cover

33116-NRA-01
Protection Cover RRI-BCA16&30



Specifications

Brand	**RedRoosterIndustrial**
Square Drive	**3/8"**
Bolt capacity (mm)	**8**
RPM	**70 - 350**
Torque (Nm)	**10 - 30**
Weight w/o battery (kg)	**1,68**
mm A	**438,9**
mm B	**38**
Battery voltage (Volt)	**18**
Battery type Li-ion….(Ah)	**2,5 / 5,0**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**0,7**
Vibration uncertainty (m/s²)	**0,2**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**65**
Sound uncertainty (dB(A))	**3**
EAN	**8717981418718**

