

# 20V-3/8" SQ, TRANSDUCER NUTRUNNER RRI-BCA30S3

RED ROOSTER Cordless transducerized angle wrench. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.

**Characteristics:**

- Brushless motor
- 20 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Tightening mode setting – Torque or Angle
- Programmable torque
- Programmable angle limits
- Programmable speed
- Group check / counting
- 8 programs including sequence
- Compact and light weight
- The flat battery pack offers stability
- Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

**Related products**



- BB200D-325  
20V 2.5Ah Battery, Li-ion
- BB200D-350  
20V 5.0Ah Battery, Li-ion
- B84192B  
18-20V Charger

**Related accessories**



- 33116-B200D-01  
Protection Cover



- 61022-TH005  
Tool Holder



- 32088-NPA-01  
Cable



- 33116-B200D-02  
Protection Cover
- 33116-NRA-01  
Protection Cover RRI-BCA16&30



**Specifications**

|                             |                      |
|-----------------------------|----------------------|
| Brand                       | RedRoosterIndustrial |
| Square Drive                | 3/8"                 |
| Bolt capacity (mm)          | 8                    |
| RPM                         | 70 - 350             |
| Torque (Nm)                 | 10 - 30              |
| Weight w/o battery (kg)     | 1,68                 |
| mm A                        | 438,9                |
| mm B                        | 38                   |
| Battery voltage (Volt)      | 20                   |
| Battery type Li-ion....(Ah) | 2,5 / 5,0            |
| Safety standard             | EN ISO 11148-6       |
| Sound standard              | ISO 15744            |
| Sound pressure (dB(A))      | < 75                 |
| Sound uncertainty (dB(A))   | 3                    |
| EAN                         | 8717981418718        |

