

# CORDLESS SHUT-OFF ANGLE WRENCH

## RRI-BA35ICA H12

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

### Characteristics:

- Brushless motor
- 18 Volt Lithium-Ion battery
- Led status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque (14-31 Nm)
- Speed 220 RPM
- in-line closed geared offset head with 12 mm Hexagon drive
- Compact and light weight


Battery and charger to be ordered separately

### Related products

-  **BB200D-325**  
18V 2.5Ah Battery, Li-ion
-  **B74SC180B**  
Programmer
-  **BB200D-350**  
18V 5.0Ah Battery, Li-ion
-  **B84192B**  
18-20V Charger
-  **E86B-VD**  
Power Cord (EU)

### Related accessories

-  **33116-B200D-01**  
Protection Cover
-  **33116-B200D-02**  
Protection Cover
-  **00-4507**  
Torque Adjust Key RRI screwdriver



### Specifications

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>RPM</b>	<b>220</b>
<b>Torque (Nm)</b>	<b>14 - 31</b>
<b>Weight (kg)</b>	<b>2,2</b>
<b>mm A</b>	<b>480</b>
<b>mm B</b>	<b>87</b>
<b>mm D</b>	<b>12</b>
<b>mm H</b>	<b>16</b>
<b>mm L</b>	<b>159</b>
<b>mm R</b>	<b>13,1</b>
<b>mm W</b>	<b>32</b>
<b>A/F (mm)</b>	<b>12</b>
<b>L1 mm</b>	<b>91</b>
<b>Battery voltage (Volt)</b>	<b>18</b>
<b>Battery type Li-ion....(Ah)</b>	<b>2,5 / 5,0</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Vibration standard</b>	<b>EN ISO 28927-2</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>12,5</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>1,5</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>68,3</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981357246</b>