

# IMPULSE WRENCH 1/2 SHUT-OFF

## RRI-80RHT

The RED ROOSTER Impulse wrenches are handheld tools made for assembly with threaded fasteners. Impulse wrenches increase productivity. Typically meant for use in: Production of agricultural machinery, production of pumps, motors, bikes and any other serial production. The tool has a wide body air motor. Torque level adjustable in the impulse mechanism.

#### Characteristics:

- Lightweight
- Free of reaction forces
- Low noise and vibration levels
- Powerful and fast
- High repeatability of the torque level
- Angled model
- Auto shut off function

#### Related accessories



70RH-RT-008

Key Wrench for 70RG, 70RH, 80RH



ATLUB

Air Tool Oil, 1 litre



#### Specifications

|   |                      |
|---|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Bolt capacity (mm)                        | 10 - 12              |
| RPM                                       | 2800                 |
| Torque (Nm)                               | 50 - 70              |
| Airconsumption (l/s)                      | 9,3                  |
| Weight (kg)                               | 1,70                 |
| Airconnection                             | PT 1/4"              |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 281                  |
| mm B                                      | 47                   |
| mm C                                      | 21                   |
| mm D                                      | 21                   |
| mm E                                      | 16                   |
| Hosediameter (mm)                         | 8                    |
| Square Drive / Hexagon                    | 1/2"                 |
| Safety standard                           | EN ISO 11148-6       |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | 8,7                  |
| Vibration uncertainty (m/s <sup>2</sup> ) | 1,35                 |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 81,7                 |
| Sound power (dB(A))                       | 92,7                 |
| Sound uncertainty (dB(A))                 | 3                    |
| EAN                                       | 8717981280650        |

