

# HIGH TORQUE GEAR WRENCH 2500 NM RRI-BEC250S

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. Version with two-hand safety control. This gear wrench has an extremely high speed.

#### Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

#### Related accessories

-  SW40-283-0102  
Hanger
-  31084-360F  
36V Charger
-  31022-GW019  
Reaction Welding Ring RRI-BEC150/250
-  Koffer RRI-BEC250  
Case RRI-BEC250
-  31022-GW001  
Reaction Bar RRI-BEC025-250
-  31022-GW008  
Sliding Reaction Plate RRI-BEC150/250
-  31022-GW010  
Reaction Bar RRI-BEC025-250
-  BW209  
Back Up Wrench 12-Pt A/F 65 mm, max  
9169 Nm
-  31022-GW007  
Secondary Handle RRI-BEC/120/150/250
-  31022-GW009  
Reaction Bar RRI-BEC025-250
-  DO6055S032  
High Torque Socket 1" x 32mm
-  31022-GW027  
double sided reaction arm
-  DO6055S065  
High Torque Socket 1"x 65mm
-  31022-GW013  
Reaction Bar Adapter RRI-BEC150/250
-  33257-RRI-BEC250  
Standard Reaction Bar RRI-BEC150/250



#### Specifications

Brand	RedRoosterIndustrial
Square Drive	1"
Bolt capacity (mm)	22 ~ 42
RPM	35 / 5
Torque (Nm)	500 ~ 2500
Weight w/o battery (kg)	6,6
mm A	170
mm B	80
mm C	368
mm D	228
mm E	273
mm F	Ø 82
mm L	70
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	1
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	82
Sound uncertainty (dB(A))	3
EAN	8717981454488

