

HIGH TORQUE GEAR WRENCH 1500 NM RRI-BEC150S

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. Version with two-hand safety control. This gear wrench has an extremely high speed. And reaches CMk > 2.5 at +/- 7% accuracy.

Characteristics:

- Brushless motor
- 36 Volt Lithium-lon battery
- LED status indicates OK NOK REVERSE BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

Related accessories



SW40-283-0102





31084-360F





31022-GW019



Reaction Welding Ring RRI-BEC150/250



31022-GW001 Reaction Bar RRI-BEC025-250



31022-GW008

Sliding Reaction Plate RRI-BEC150/250

D06055S055

High Torque Socket 1" x 55mm



31022-GW010





D06055S030

High Torque Socket 1" x 30mm



Koffer RRI-BEC150 Case RRI-BEC150



31022-GW007



Secondary Handle RRI-BEC/120/150/250



31022-GW009 Reaction Bar RRI-BEC025-250



BW203

Back Up Wrench 12-Pt A/F 55 mm, max 5694 Nm 31022-GW013



Reaction Bar Adapter RRI-BEC150/250



33257-RRI-BEC250

Standard Reaction Bar RRI-BEC150/250
DOESR-3

Ret Ring





Specifications

| Brand | RedRoosterIndustrial |
|-------------------------|----------------------|
| Square Drive | 1" |
| Bolt capacity (mm) | 20 ~ 36 |
| RPM | 45 / 9,6 |
| Torque (Nm) | 300 ~ 1500 |
| Weight w/o battery (kg) | 6,2 |
| Sound level (dB(A)) | < 80 |
| mm A | 170 |
| mm B | 80 |
| mm C | 355 |
| mm D | 228 |
| mm E | 273 |
| mm F | Ø 82 |
| mm L | 70 |
| Battery voltage (Volt) | 36 |
| Battery type Li-ion(Ah) | 5,0 |
| EAN | 8717981454471 |
| | |

