

# DIE GRINDER 45000 RPM RRI-3445

## Characteristics:

- \* The compact collet chuck and nut are designed for industrial work in confined spaces.
- \* The chuck takes 6 mm shafts and 3 mm shafts
- \* The exhaust air is redirected from the user through a hose with muffler
- \* The rubber cover of the motorhousing isolates against cold and vibrations
- \* The grinders have a safety lever

## Related products



AC30A-F03E-B  
Modular FRL Unit

## Related accessories



ATLUB  
Air Tool Oil, 1 litre



## Specifications

Brand	RedRoosterIndustrial
RPM	45000
Airconsumption (l/s)	7,5
Weight (kg)	0,40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	190
mm B	34
mm C	14
mm D	16
mm E	22
Hosediameter (mm)	10
Collet chuck (mm)	3 / 6
Power (kW)	0,30
Wheel size (mm)	20
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-12
Vibration value (m/s <sup>2</sup> )	< 2,5
Vibration uncertainty (m/s <sup>2</sup> )	0,69
Sound standard	ISO 15744
Sound pressure (dB(A))	82,3
Sound power (dB(A))	83,3
Sound uncertainty (dB(A))	3
EAN	8717981024384

