

DIE GRINDER 45000 RPM

RRI-3445

Characteristics:

- * The compact collet chuck and nut are designed for industrial work in confined spaces.
- * The chuck takes 6 mm shafts and 3 mm shafts
- * The exhaust air is redirected from the user through a hose with muffler
- * The rubber cover of the motorhousing isolates against cold and vibrations
- * The grinders have a safety lever

Related products



AC30A-F03E-B

Modular FRL Unit



Related accessories



ATLUB

Air Tool Oil, 1 litre

Specifications

| | |
|--|-----------------------------|
| Brand | RedRoosterIndustrial |
| RPM | 45000 |
| Airconsumption (l/s) | 7,5 |
| Weight (kg) | 0,40 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 190 |
| mm B | 34 |
| mm C | 14 |
| mm D | 16 |
| mm E | 22 |
| Hosediameter (mm) | 10 |
| Collet chuck (mm) | 3 / 6 |
| Power (kW) | 0,30 |
| Wheel size (mm) | 20 |
| Safety standard | EN ISO 11148-7 |
| Vibration standard | EN ISO 28927-12 |
| Vibration value (m/s²) | < 2,5 |
| Vibration uncertainty (m/s²) | 0,69 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 82,3 |
| Sound power (dB(A)) | 83,3 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981024384 |

