

DIE GRINDER 45000 RPM RRI-3445

Characteristics:

- * The compact collet chuck and nut are designed for industrial work in confined spaces.
- * The chuck takes 6 mm shafts and 3 mm shafts
- * The exhaust air is redirected from the user through a hose with muffler
- * The rubber cover of the motorhousing isolates against cold and vibrations
- * The grinders have a safety lever

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	RedRoosterIndustrial
RPM	45000
Airconsumption (l/s)	7,5
Weight (kg)	0,40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	190
mm B	34
mm C	14
mm D	16
mm E	22
Hosediameter (mm)	10
Collet chuck (mm)	3 / 6
Power (kW)	0,30
Wheel size (mm)	20
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-12
Vibration value (m/s ²)	< 2,5
Vibration uncertainty (m/s ²)	0,69
Sound standard	ISO 15744
Sound pressure (dB(A))	82,3
Sound power (dB(A))	83,3
Sound uncertainty (dB(A))	3
EAN	8717981024384

