

AUTO-SHUT-OFF SCREWDRIVER 14~22NM ATEX RRI-SA50322W-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIIB T135°C.

Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

Related products



TW-3C Spring balancer 1,0-3,0 kg

AC30A-F03E-B Modular FRL Unit

Related accessories

00-4507 Torque Adjust Key RRI screwdriver ATLUB



Air Tool Oil, 1 litre



Specifications

| Brand | RedRoosterIndustrial |
|------------------------|----------------------|
| Square Drive | 3/8" |
| Bolt capacity (mm) | 6 |
| RPM | 320 |
| Torque (Nm) | 14,0 ~ 22,0 |
| Airconsumption (I/s) | 11 |
| Weight (kg) | 1,81 |
| Sound level (dB(A)) | 74 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 369 |
| mm B | 38 |
| mm C | 14 |
| mm D | 16 |
| mm E | 3/8" |
| Hosediameter (mm) | 6,5 |
| Execution | Angle |
| Vibration level (m/s²) | < 2,5 |
| Safety standard | EN ISO 11148-6 |
| EAN | 8717981461059 |
| | |

