

COMPOSITE IMPACT WRENCH 3/4 RRI-2500ML

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-2500M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use. Breakloose torque: 2.700 Nm.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- · Power adjustable, 2 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown
- Long anvil

Related products



D0605421001

Impact Socket Set 3/4" deep 10p



D0605401001

Socketset 3/4" 10-Parts

Related accessories



DOESR-2

Ret Ring



DOESR-1 Ret Ring



Specifications

 Square Drive
 3/4"

 Version
 R+H

 Bolt capacity (mm)
 24

 Impact mechanism
 Mechaneer

 RPM
 5500

 Torque (Nm)
 2000

 Force adjustment
 L/R 2 Pos.

 Airconsumption (I/s)
 16

 Weight (kg)
 3.7

 Weight (kg)
 3,7

 Airconnection
 3/8"

 Airpress max. (MPa)
 0,63

 mm A
 313

 mm B
 45

 Hosediameter (mm)
 13

Safety standard EN ISO 11148-6

Max. breakaway torque (Nm) 2700

Vibration standard EN ISO 28927-2

 Vibration value (m/s²)
 7

 Vibration uncertainty (m/s²)
 1,19

 Sound standard
 ISO 15744

 Sound pressure (dB(A))
 88,4

 Sound power (dB(A))
 99,4

 Sound uncertainty (dB(A))
 3

EAN 8717981425693

