

HIGH TORQUE GEAR WRENCH 2500 NM

RRI-BEC250

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. This gear wrench has an extremely high speed. And reaches CMk > 2,5 at +/- 7% accuracy.

Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

Related accessories

-  SW40-283-0102
Hanger
-  31084-360F
36V Charger
-  31022-GW019
Reaction Welding Ring RRI-BEC150/250
-  Koffer RRI-BEC250
-  Case RRI-BEC250
-  31022-GW001
Reaction Bar RRI-BEC025-250
-  31022-GW008
Sliding Reaction Plate RRI-BEC150/250
-  31022-GW010
Reaction Bar RRI-BEC025-250
-  BW209
Back Up Wrench 12-Pt A/F 65 mm, max 6169 Nm
-  31022-GW007
Secondary Handle RRI-BEC/120/150/250
-  31022-GW009
Reaction Bar RRI-BEC025-250
-  DO6055S032
High Torque Socket 1" x 32mm
-  DO6055S065
High Torque Socket 1"x 65mm
-  31022-GW013
Reaction Bar Adapter RRI-BEC150/250
-  33257-RRI-BEC250
Standard Reaction Bar RRI-BEC150/250
-  DOESR-3
Ret Ring



Specifications

Brand	RedRoosterIndustrial
Square Drive	1"
Bolt capacity (mm)	22 ~ 42
RPM	35 / 5
Torque (Nm)	500 ~ 2500
Weight w/o battery (kg)	6,6
Sound level (dB(A))	<80
mm A	170
mm B	80
mm C	368
mm D	228
mm E	273
mm F	Ø 82
mm L	70
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
EAN	8717981444106

