

# HIGH TORQUE GEAR WRENCH 2500 NM

## RRI-BEC250

RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. This gear wrench has an extremely high speed. And reaches CMk > 2,5 at +/- 7% accuracy.

### Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Batteries, charger and other accessories must be ordered separately.

### Related accessories

	<b>SW40-283-0102</b>
	<b>Hanger</b>
	<b>31084-360F</b>
	<b>36V Charger</b>
	<b>31022-GW019</b>
	<b>Reaction Welding Ring RRI-BEC150/250</b>
	<b>Koffer RRI-BEC250</b>
	<b>Case RRI-BEC250</b>
	<b>31022-GW001</b>
	<b>Reaction Bar RRI-BEC025-250</b>
	<b>31022-GW008</b>
	<b>Sliding Reaction Plate RRI-BEC150/250</b>
	<b>31022-GW010</b>
	<b>Reaction Bar RRI-BEC025-250</b>
	<b>BW209</b>
	<b>Back Up Wrench 12-Pt A/F 65 mm, max 6169 Nm</b>
	<b>31022-GW007</b>
	<b>Secondary Handle RRI-BEC/120/150/250</b>
	<b>31022-GW009</b>
	<b>Reaction Bar RRI-BEC025-250</b>
	<b>D06055S032</b>
	<b>High Torque Socket 1" x 32mm</b>
	<b>31022-GW027</b>
	<b>double sided reaction arm</b>
	<b>D06055S065</b>
	<b>High Torque Socket 1" x 65mm</b>
	<b>31022-GW013</b>
	<b>Reaction Bar Adapter RRI-BEC150/250</b>
	<b>33257-RRI-BEC250</b>
	<b>Standard Reaction Bar RRI-BEC150/250</b>



### Specifications

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>Square Drive</b>	<b>1"</b>
<b>Bolt capacity (mm)</b>	<b>22 ~ 42</b>
<b>RPM</b>	<b>35 / 5</b>
<b>Torque (Nm)</b>	<b>500 ~ 2500</b>
<b>Weight w/o battery (kg)</b>	<b>6,6</b>
<b>Sound level (dB(A))</b>	<b>&lt;80</b>
<b>mm A</b>	<b>170</b>
<b>mm B</b>	<b>80</b>
<b>mm C</b>	<b>368</b>
<b>mm D</b>	<b>228</b>
<b>mm E</b>	<b>273</b>
<b>mm F</b>	<b>Ø 82</b>
<b>mm L</b>	<b>70</b>
<b>Battery voltage (Volt)</b>	<b>36</b>
<b>Battery type Li-ion....(Ah)</b>	<b>5,0</b>
<b>EAN</b>	<b>8717981444106</b>

