# ELECTRIC SCREWDRIVER 1,47~2,94NM
# RRI-ESL71930

**The RED ROOSTER electrical brushless screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design including ESD safe body material. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This corded tool is designed for the assembly industry, where threaded fasteners are used.**
**Delivery includes: Standard power controller, AC cord and DC cord, clutch cover.**
**Characteristics:**
- **soft ergonomic grip, lever start**
- **starting lever is contactless which allows for high durability**
- **stepless adjustable torque level**
- **the optional clutch cover can prevent unauthorized torque adjustment**



## Related accessories



**DE7L-1078**
**Grip (For lever start)**



**DE7L-0024**
**Tool Holder**



**RRI-DE7L-8301B**
**Advanced power controller**



**DE7L-2026**
**Clutch Housing Cover**



**TW-0**
**Spring Balancer 0,5-1,5kg**



**DE7L-0012**
**Torque Adjustment Tool**



**RRI-DE7L-8301**
**Power controller**

## Specifications

| | |
|---|---|
| **Brand** | **RedRoosterIndustrial** |
| **Bolt capacity (mm)** | **3,5** |
| **RPM** | **1900** |
| **Torque (Nm)** | **1,47 ~ 2,94** |
| **Weight (kg)** | **0,85** |
| **Bitchuck** | **1/4" HEX** |
| **L mm** | **306,9** |
| **ESD compliance** | **EN IEC 61000-4-2** |
| **Vibration standard** | **EN ISO 28927-2** |
| **Vibration value (m/s²)** | **0,2** |
| **Vibration uncertainty (m/s²)** | **0,1** |
| **Sound standard** | **ISO 15744** |
| **Sound pressure (dB(A))** | **63** |
| **Sound uncertainty (dB(A))** | **3** |
| **EAN** | **8717981470549** |

