

AUTO-SHUT-OFF SCREWDRIVER RRI-SL30512

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

Related products



AC30A-F03E-B
Modular FRL Unit

HTB-0
Spring Balancer Hosereel

Related accessories



00-4507
Torque Adjust Key RRI screwdriver



ATLUB
Air Tool Oil, 1 litre



Specifications

| | |
|-------------------------------------|------------------------|
| Brand | RedRoosterIndustrial |
| Bolt capacity (mm) | 6 |
| RPM | 500 |
| Torque (Nm) | 4,0 - 11,0 |
| Airconsumption (l/s) | 11 |
| Weight (kg) | 0,98 |
| Hexagon | 1/4" |
| Sound level (dB(A)) | 73 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 299 |
| mm B | 39 |
| mm C | 16 |
| mm D | 15 |
| Hosediameter (mm) | 6,5 |
| Execution | Straight - lever start |
| Vibration level (m/s ²) | < 2,5 |
| Safety standard | EN ISO 11148-6 |
| EAN | 8717981414451 |

