

COMPOSITE IMPACT WRENCH 1/2

RRI-2100M

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-2100M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use.
Breakloose torque: 1.850 Nm.




Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- Power adjustable, 2 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown

Related products

-  DO605201003
Impact Socket Set 1/2" 10-parts
-  DO691121301
Impact Socket Set 1/2" & bits 13-parts
-  DO69523108
Impact Socket Set 1/2" deep 10-parts
-  DO605202602
Impact Socket Set 1/2" 26-parts
-  DO652260701
Impact Socket Set 1/2" triple square

Related accessories

-  EH-43-4033SUB
Exhaust Hose Assembly 1/4"
-  61022-TH004
Tool Holder, diameter 73mm
-  ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	RedRoosterIndustrial
Square Drive	1/2"
Version	R
Bolt capacity (mm)	20
Impact mechanism	Mechoneer
RPM	7500
Torque (Nm)	1000
Force adjustment	L/R 2 Pos
Airconsumption (l/s)	12
Weight (kg)	2,0
Airconnection	PT 1/4
Airpress max. (MPa)	0,63
mm A	162
mm B	36
Hosediameter (mm)	10
Max. breakaway torque (Nm)	1850
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	6,5
Vibration uncertainty (m/s ²)	1,14
Sound standard	ISO 15744
Sound pressure (dB(A))	88,2
Sound power (dB(A))	99,2
Sound uncertainty (dB(A))	3
EAN	8717981400799

